

H07Z-U 单芯无护套实心导体交联聚乙烯绝缘布线



Description	说明
<ul style="list-style-type: none"> ● Rate temperature: 90°C ● Rate voltage: 450/750V ● Standard: DIN VDE 0282-9:2007-12,HD22.9 S3:2007 ● Class1 requirement given in EN 60228 ● The insulation shall be a polyolefin cross-linked material T,type EI 5 to EN 50363-5 	<ul style="list-style-type: none"> ● 额定温度：90°C ● 额定电压：450/750V ● 参考标准：DIN VDE 0282-9:2007-12,HD22.9 S3:2007 ● 导体使用标准 EN60228 中要求的第一类导体 ● 绝缘材料使用符合标准 EN50363-5 的 EI5 型要求的交联聚乙烯

Application	应用
General-purpose type electrical appliances, equipment Internal fixation wiring	一般用途类电器、设备内部固定布线

No. 编号	Conductor 导体结构		绝缘厚度		MAX.COND.RESISANCE 最大导体直流电阻 (Ω/Km,20°C, DC)	APPROX WEIGHT 参 考重量 (Kg/Km)
	规格 (mm ²)	CONSTRUCYION 结构 (NO./mm)	THICKNESS 厚度 (mm)	O.D. 外径 (mm)		
HU01150	1.5	1/1.38	0.7	2.9±0.15	12.1	20.7
HU01250	2.5	1/1.78	0.8	3.5±0.15	7.41	32.7
HU01400	4.0	1/2.25	0.8	3.9±0.20	4.61	48.4
HU01600	6.0	1/2.76	0.8	4.4±0.20	3.08	68.6
HU01A00	10	1/3.55	1.0	5.6±0.25	1.83	110.1