



## Description

- Rated temperature: 70°C
- Rated voltage: 0.6/1.0KV (Inclusion 300/500V, 450/750V)
- Reference standard: DIN0281, EN50525
- Conductor: Soft-annealed tinned or bare copper wire
- Insulation: polrvinyl chloride (PVC)
- Shield: Optional
- Jacket: polrvinyl chloride (PVC)

## 说明

- 额定温度：70°C
- 额定电压：0.6/1.0KV以下(包含300/500V、450/750V)
- 参考标准：DIN0281, EN50525
- 导体类型：退火软镀锡或裸圆铜线
- 绝缘材料：聚氯乙烯 (PVC)
- 屏蔽：可选择是否屏蔽
- 护套材料：聚氯乙烯 (PVC)

## Application

For fixed occasions such as indoor ,cable chute,Pipeline and where anti-interference is required Etc.(2-40CORES 0.5-2.5 mm<sup>2</sup>, 2-12CORES 4-70 mm<sup>2</sup>)

## 应用

用于控制、监控联锁回路及保护线路等场所，安装在室内、移动要求柔软的场所(2-40芯 0.5-2.5 mm<sup>2</sup>， 2-12芯 4-70 mm<sup>2</sup>)

NO. 编号	CORE 芯数	Conductor 导体		Insulation 绝缘		Jacket 护套		Max. Resistance at 20°C 最大导体电阻 (Ω/km)	Re. weight 参考重量 (Kg/Km)
		Section 截面积 (mm <sup>2</sup> )	Structure 结构 (mm)	Thick 厚度 (mm)	Nom. dia. 外径 (mm)	Thick 厚度 (mm)	Nom. dia. 外径 (mm)		
JZ05050	2	0.5	28/0.15	0.6	2.15±0.15	0.8	7.5±0.25	39.0	88
JZ10075	10	0.75	42/0.15	0.6	2.35±0.15	1.2	12.0±0.60	26.0	225
JZ16150	16	1.5	48/0.20	0.7	3.05±0.15	1.2	16.1±0.80	13.3	454.2
JZ04A00	4	10	140/0.30	1.0	6.6±0.15	1.8	20.0±0.80	1.91	710.8
JZ04B50	4	25	196/0.40	1.2	10.0±0.25	2.0	28.5±1.50	0.780	1611.3
JZ07A00	7	10	140/0.30	1.0	6.6±0.25	2.0	24.5±1.00	1.91	1227.5